

Specification	POELSAN®			Competitor 1			Competitor 2		
	1"	1½"	2"	1"	1½"	2"	1"	1½"	2"
Product Pressure Range (Bar)	1,0 - 10	1,0 - 10	1,0 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,04 - 10,4	1,4 - 10,4	1,4 - 10,4
Flow Rate (m³/h)	0,05 - 9	5,0 - 27	5,0 - 34	0,05 - 9	4,5 - 27	4,5 - 34	0,5 - 9	6 - 21	9 - 34
Flow Control	✗	✓	✓	Optional	✓	✓	✓	✓	✓
Coil Type (9V–24V)	✓	✓	✓	✓	✓	✓	Separate	Common	Common
Common Bolt Head	✓	✓	✓	✓	✓	✓	✗	✗	✗
3-Way Valve	✗	✓	✓	✗	✓	✓	✗	✓	✓
Manual Opening Option	✓	✓	✓	✓	✓	✓	✓	✓	✓
Bolts	Hex Head Screw			Hex Head Phillips Screw			Hex Head Phillips Screw		
Pressure Regulator	Not Available			Optional			Optional		
Thread Type	BSP - NPT			BSP - NPT			BSP - NPT		
Temperature Rating (°C)	66			66			52		
Warranty Period (Years)	2			2			3		